LED Eco Exit Maintained Emergency Exit

Catalogue No:

F9920L

Description:

LED Wall or Ceiling Mounted Emergency Exit Luminaire.

Fast Fit Bracket & Connector for Ease of Installation.

Extruded Aluminium Body with Slim Compact Styling
High Emergency Classification.

Available Options:


F9920L/SS/* Single Sided F9920L/DS/* Double Sided

* denotes:

/E 'EXIT' with Peel Off Arrows /RMS Running Man Exit Straight /RML Running Man Exit Arrow Left /RMR Running Man Exit Arrow Right

Australian conceived, designed & manufactured.





www.famco.com.au

MAXIMUM PERMISSIBLE SPACING FOR EMERGENCY LUMINAIRES																		
PHOTOMETRIC CLASSIFICATION			MOUNTING HEIGHT - M															
			2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5	6	7	8	9	10	15	20
F9920L/SS	C0	D3.2	6.5	6.6	6.6	6.5	6.4	6.2	5.8	5.1	4.1							
	C90	E2	5.2	5.2	5.4	5.2	5.0	4.6	4.8	4.0								
F9920L/DS	C0	D3.2	6.5	6.6	6.6	6.5	6.4	6.2	5.8	5.1	4.1							
	C90	E2.5	5.6	5.8	5.8	6.0	5.8	5.8	5.2	5.2	4.6							



P. +64 7 544 7403

E. sales@antipodesled.co.nz

W. www.antipodesled.co.nz